



GTS 29

HIGH-PERFORMANCE FLYABLE SUBWOOFER



Description The GTS 29 is a dual 19" subwoofer module for the low-frequency extension in high-demanding touring and install applications, indoors and outdoors. Equipped with two high-excursion best-in-class transducers, it offers excellent reproduction quality and extreme sound pressure. The cabinet is provided with power connections on front and back panels for easy deployment in cardioid configuration. Up to 16 GTS 29 modules can be ground-stacked or flown on a single fly-bar.

- Features**
- › 144 dB max SPL
 - › 2 x 19" neo woofers, 4" v.c.
 - › 3 side handles
 - › Designed to operate with XPS 16K amplifier (4 modules per amp unit)
 - › Durable and lightweight cabinet construction, polyurea coating
 - › Heavy duty, powder coated, custom perforated front grille
 - › 2 x 2 P-COM 8 pole bayonet connectors (Gold coated, CA-COM compatible, IP 68)

Part Number 13000820 GTS 29 Black EAN 8024530021245



GTS 29

HIGH-PERFORMANCE FLYABLE SUBWOOFER

Acoustical specifications	Frequency Response (-10dB)	25 Hz ÷ 200 Hz
	Max SPL @ 1m	144 dB
Power section	Amplification	Full Range
	Nominal Impedance LF	8 ohm
	Nominal Impedance LF2	8 ohm
Transducers	Woofer	2 x 19" neo, 4.0" v.c
Input/Output section	Input connectors	P-COM 8POLE
	Output connectors	P-COM 8POLE
Standard compliance	Safety agency	CE compliant
Physical specifications	Hardware	Suspension Fittings, M20 Socket
	Handles	3 x side
	Color	Black
Size	Height	531.5 mm / 20.93 inches
	Width	1310 mm / 51.57 inches
	Depth	735 mm / 28.94 inches
	Weight	96 kg / 211.64 lbs

Line Art 2D

