




CS 6520EN

TWO-WAY COLUMN SPEAKER



Description

CS 6520EN is a compact and elegant two-way column speaker providing highly intelligible voice reproduction, and suitable for installation into places of worship, stations, subways and many other environments. The terminal connection blocks, for input and output flameproof cables, are made of ceramic material. A thermal fuse protects the integrity of the line in case of heat affecting the speaker. Ground screw available (if needed). Thanks to its IP66 protection grade, it can be installed both indoor and outdoor.

Features

- › 4 x 3" fullrange transducers with 0.75" dome tweeter.
- › Power selectable (100 V): 20 W - 10 W - 5 W - 2.5 W - 1.25 W.
- › 93 dB sensitivity.
- › Colour white RAL 9003.
- › Aluminium body, grille and bracket.
- › In/out ceramic terminal block.
- › Thermal fuse protection.
- › Protection grade IP66.

Part Number

13133079 CS 6520EN


White - RAL 9003 EAN 8024530010478



CS 6520EN

TWO-WAY COLUMN SPEAKER

Line Art 2D



TECHNICAL SPECIFICATIONS

Acoustical specifications	Frequency Response (-10dB)	140 Hz ÷ 20000 Hz
	Max SPL @ 1m	105 dB
	Max SPL @ 4m	93 dB
	Horizontal coverage angle	185°
	Vertical coverage angle	47°
	System Sensitivity	93 dB
Power section	System Sensitivity 1W @ 4m	81 dB
	Amplification	Full Range
	Power Handling	20 W
	Peak Power Handling	80 W PEAK
	Protections	Thermal fuse
Transducers	Recommended Amplifiers	DXT 3000, DXT 4000, DXT 7000
	Dome Tweeter	1 x 0.75"
	Fullrange	4 x 3.0"
Input/Output section	Input connectors	Ceramic screw terminals
	Output connectors	Ceramic screw terminals
	Constant Voltage Transformer	70/100 V
	Power selection 1	20 W - 500 ohm
	Power selection 2	10 W - 1000 ohm
	Power selection 3	5 W - 2000 ohm
Standard compliance	Power selection 4	2.5 W - 4000 ohm
	Power selection 5	1.25 W - 8000 ohm
	IP protection grade	IP 66
	Safety agency	CE compliant
	EN54-24 certified	Yes
Physical specifications	CPR number	1488-CPR-0490/W
	Cabinet/Case Material	Aluminum
	Grille	Aluminium
	Color	White - RAL 9003



CS 6520EN

TWO-WAY COLUMN SPEAKER

Size	Height	620 mm / 24.41 inches
	Width	114 mm / 4.49 inches
	Depth	96 mm / 3.78 inches
	Weight	4.2 kg / 9.26 lbs