

# S 4022

# BANDPASS SUBWOOFER

## **DESCRIPTION**

The S4022 is a compact, high-output bandpass subwoofer dedicated to permanent installations.

The system is equipped with two advanced 12" RCF precision woofers mounted in a clamshell internal chamber. The two transducers couple to achieve tight and maximised output. Each 12" features massive ceramic magnets and 3" copper voice coil. The system is capable of producing a Max SPL of 131 dB and handles 800 Watts AES.



#### **FEATURES**

- Compact, arrayable, 2 x 12" bandpass subwoofer system
- 131 dB max SPL, 800 Watt AES
- Equipped with RCF high power 2 x12", 3" voice coil woofers
- Extensive internal bracing, 8 x M10 mounting points
- Recessed handles
- Baltic Birch cabinet finished in a very resistant, textured, polyurethane black paint
- Epoxy powder coated front grille
- Dedicated to permanent installation

Rev. C Last update: 26/11/2020



## **TECHNICAL SPECIFICATIONS**

Acoustical specifications	Frequency Response (-10dB):	40 Hz ÷ 200 Hz
	Max SPL @ 1m:	131 dB
	System Sensitivity:	97 dB
Power section	Nominal Impedance (ohm):	4 ohm
	Power Handling:	800 W RMS
	Peak Power Handling:	3200 W PEAK
	Recommended Amplifier:	1600 W
Transducers	Woofer:	2 x 12", 3.0" v.c
	Nominal Impedance (ohm):	8 ohm
	Input Power Rating:	400 W AES, 800 W PROGRAM POWER
	Sensitivity:	97 dB, 1W @ 1m
Input/Output section	Input connectors:	Speakon® NL4
Standard compliance	CE marking:	Yes
Physical specifications	Cabinet/Case Material:	Baltic birch plywood
	Hardware:	8 x m10 mounting points, 2 x recessed
	Grille:	Steel
Size	Height:	500 mm / 19.69 inches
	Width:	650 mm / 25.59 inches
	Depth:	580 mm / 22.83 inches
	Weight:	45 kg / 99.21 lbs
Shipping informations	Package Height:	580 mm / 22.83 inches
	Package Width:	740 mm / 29.13 inches
	Package Depth:	660 mm / 25.98 inches
	Package Weight:	52 kg / 114.64 lbs

# **PART NUMBER**

· 13000082

S 4022

EAN 8024530007966