CVR HD 12-32

PROTECTION COVER

DESCRIPTION

Protection cover. It features heavy-duty polyester outer fabric, foam rubber padding, and zip openings with Velcro fasteners.

FEATURES

- Outer fabric: 600D polyester on PVC base
- Internal fabric: 190 T taffeta fabric on PVC base
- Padding: 10 mm foam rubber
- Closure / opening: frontal and rear Zip + Velcro
- Embroidered white logo on front
- Handle hole on sides

TECHNICAL SPECIFICATIONS

General specifications	Protections	Scratches, hits
	Material	Nylon
Standard compliance	EN54-4 certified:	Yes
	CE compliance:	Yes
Physical specifications	Color:	Black
Size	Weight:	1.29 kg / 2.84 lbs
Shipping informations	Package Height:	90 mm / 3.54 inches
	Package Width:	720 mm / 28.35 inches
	Package Depth:	400 mm / 15.75 inches
	Package Weight:	1.45 kg / 3.2 lbs

PART NUMBER

- **13360209**

  CVR HD 12-32

  EAN 8024530010720

RCF products are continually improved. All specifications are therefore subject to change without notice.


Response 1W/1m
dB SPL
110
100
90
80
70
60
20
100
1000
10000
Frequency (Hz)


Impedance
Ohms
316
100
10
1
100
1000
10000
Frequency (Hz)


Beamwidth vs. Frequency
Coverage Angle (Deg.)
360
330
300
270
240
210
180
150
120
90
60
30
0
Horizontal Beamwidth (1/3 Octave)
Vertical Beamwidth (1/3 Octave)
100
1000
10000
Frequency (Hz)


Directivity Index and Q
Total Q
Directivity index DI, dB
100
10
1
20
18
16
14
12
10
8
6
4
2
0
100
1000
10000
Frequency (Hz)


Normalized Horizontal off-axis Response
Attenuation in dB
5
0
-5
-10
-15
-20
-25
-30
Horizontal ±10 degrees
Horizontal ±20 degrees
Horizontal ±30 degrees
Horizontal ±40 degrees
Horizontal ±50 degrees
Horizontal ±60 degrees
100
1000
10000
Frequency (Hz)


Normalized Vertical off-axis Response. Above the box
Attenuation in dB
5
0
-5
-10
-15
-20
-25
-30
Vertical +10 degrees
Vertical +20 degrees
Vertical +30 degrees
Vertical +40 degrees
Vertical +50 degrees
Vertical +60 degrees
100
1000
10000
Frequency (Hz)


Normalized Vertical off-axis Response. Below the box
Attenuation in dB
5
0
-5
-10
-15
-20
-25
-30
Vertical -10 degrees
Vertical -20 degrees
Vertical -30 degrees
Vertical -40 degrees
Vertical -50 degrees
Vertical -60 degrees
100
1000
10000
Frequency (Hz)


Horizontal 1/3 Octave Polars
160
125
100


Horizontal 1/3 Octave Polars
315
250
200


Horizontal 1/3 Octave Polars
630
500
400


Horizontal 1/3 Octave Polars
1250
1000
800


Horizontal 1/3 Octave Polars
2500
2000
1600


Horizontal 1/3 Octave Polars
5000
4000
3150


Horizontal 1/3 Octave Polars
10000
8000
6300


Horizontal One Octave Polars


Vertical 1/3 Octave Polars
160
125
100


Vertical 1/3 Octave Polars
315
250
200


Vertical 1/3 Octave Polars
630
500
400


Vertical 1/3 Octave Polars
1250
1000
800


Vertical 1/3 Octave Polars
2500
2000
1600


Vertical 1/3 Octave Polars
5000
4000
3150


Vertical 1/3 Octave Polars
10000
8000
6300


Vertical One Octave Polars


Response 1W/1m
dB SPL
110
100
90
80
70
60
20
100
1000
10000
Frequency (Hz)


Impedance
Ohms
316
100
10
1
100
1000
10000
Frequency (Hz)


Beamwidth vs. Frequency
Coverage Angle (Deg.)
360
330
300
270
240
210
180
150
120
90
60
30
0
100
1000
10000
Frequency (Hz)
Horizontal Beamwidth (1/3 Octave)
Vertical Beamwidth (1/3 Octave)


Directivity Index and Q
Total Q
Directivity index DI, dB
100
10
1
20
18
16
14
12
10
8
6
4
2
0
100
1000
10000
Frequency (Hz)


Normalized Horizontal off-axis Response
Attenuation in dB
5
0
-5
-10
-15
-20
-25
-30
100
1000
10000
Frequency (Hz)
Horizontal ±10 degrees
Horizontal ±20 degrees
Horizontal ±30 degrees
Horizontal ±40 degrees
Horizontal ±50 degrees
Horizontal ±60 degrees


Normalized Vertical off-axis Response. Above the box
Attenuation in dB
5
0
-5
-10
-15
-20
-25
-30
100
1000
10000
Frequency (Hz)
Vertical +10 degrees
Vertical +20 degrees
Vertical +30 degrees
Vertical +40 degrees
Vertical +50 degrees
Vertical +60 degrees


Normalized Vertical off-axis Response. Below the box
Attenuation in dB
5
0
-5
-10
-15
-20
-25
-30
100
1000
10000
Frequency (Hz)
Vertical -10 degrees
Vertical -20 degrees
Vertical -30 degrees
Vertical -40 degrees
Vertical -50 degrees
Vertical -60 degrees


Horizontal 1/3 Octave Polars
160
125
100


Horizontal 1/3 Octave Polars
315
250
200


Horizontal 1/3 Octave Polars
630
500
400


Horizontal 1/3 Octave Polars
1250
1000
800


Horizontal 1/3 Octave Polars
2500
2000
1600


Horizontal 1/3 Octave Polars
5000
4000
3150


Horizontal 1/3 Octave Polars
10000
8000
6300


Horizontal One Octave Polars


Vertical 1/3 Octave Polars
160
125
100


Vertical 1/3 Octave Polars
315
250
200


Vertical 1/3 Octave Polars
630
500
400


Vertical 1/3 Octave Polars
1250
1000
800


Vertical 1/3 Octave Polars
2500
2000
1600


Vertical 1/3 Octave Polars
5000
4000
3150


Vertical 1/3 Octave Polars
10000
8000
6300


Vertical One Octave Polars


Response 1W/1m
dB SPL
110
100
90
80
70
60
20
100
1000
10000
Frequency (Hz)


Impedance
Ohms
316
100
10
1
100
1000
10000
Frequency (Hz)


Beamwidth vs. Frequency
Coverage Angle (Deg.)
360
330
300
270
240
210
180
150
120
90
60
30
0
100
1000
10000
Frequency (Hz)
Horizontal Beamwidth (1/3 Octave)
Vertical Beamwidth (1/3 Octave)


Directivity Index and Q
Total Q
Directivity index DI, dB
100
10
1
20
18
16
14
12
10
8
6
4
2
0
100
1000
10000
Frequency (Hz)


Normalized Horizontal off-axis Response
Attenuation in dB
5
0
-5
-10
-15
-20
-25
-30
100
1000
10000
Frequency (Hz)
Horizontal ±10 degrees
Horizontal ±20 degrees
Horizontal ±30 degrees
Horizontal ±40 degrees
Horizontal ±50 degrees
Horizontal ±60 degrees


Normalized Vertical off-axis Response. Above the box
Attenuation in dB
5
0
-5
-10
-15
-20
-25
-30
100
1000
10000
Frequency (Hz)
Vertical +10 degrees
Vertical +20 degrees
Vertical +30 degrees
Vertical +40 degrees
Vertical +50 degrees
Vertical +60 degrees


Normalized Vertical off-axis Response. Below the box
Attenuation in dB
5
0
-5
-10
-15
-20
-25
-30
100
1000
10000
Frequency (Hz)
Vertical -10 degrees
Vertical -20 degrees
Vertical -30 degrees
Vertical -40 degrees
Vertical -50 degrees
Vertical -60 degrees


Horizontal 1/3 Octave Polars
160
125
100


Horizontal 1/3 Octave Polars
315
250
200


Horizontal 1/3 Octave Polars
630
500
400


Horizontal 1/3 Octave Polars
1250
1000
800


Horizontal 1/3 Octave Polars
2500
2000
1600


Horizontal 1/3 Octave Polars
5000
4000
3150


Horizontal 1/3 Octave Polars
10000
8000
6300


Horizontal One Octave Polars


Vertical 1/3 Octave Polars
160
125
100


Vertical 1/3 Octave Polars
315
250
200


Vertical 1/3 Octave Polars
630
500
400


Vertical 1/3 Octave Polars
1250
1000
800


Vertical 1/3 Octave Polars
2500
2000
1600


Vertical 1/3 Octave Polars
5000
4000
3150


Vertical 1/3 Octave Polars
10000
8000
6300


Vertical One Octave Polars


Response 1W/1m
dB SPL
110
100
90
80
70
60
20
100
1000
10000
Frequency (Hz)


Impedance
Ohms
316
100
10
1
100
1000
10000
Frequency (Hz)


Beamwidth vs. Frequency
Coverage Angle (Deg.)
360
330
300
270
240
210
180
150
120
90
60
30
0
Horizontal Beamwidth (1/3 Octave)
Vertical Beamwidth (1/3 Octave)
100
1000
10000
Frequency (Hz)


Directivity Index and Q
Total Q
Directivity index DI, dB
100
10
1
20
18
16
14
12
10
8
6
4
2
0
100
1000
10000
Frequency (Hz)


Normalized Horizontal off-axis Response
Attenuation in dB
5
0
-5
-10
-15
-20
-25
-30
Horizontal ±10 degrees
Horizontal ±20 degrees
Horizontal ±30 degrees
Horizontal ±40 degrees
Horizontal ±50 degrees
Horizontal ±60 degrees
100
1000
10000
Frequency (Hz)


Normalized Vertical off-axis Response. Above the box
Attenuation in dB
5
0
-5
-10
-15
-20
-25
-30
Vertical +10 degrees
Vertical +20 degrees
Vertical +30 degrees
Vertical +40 degrees
Vertical +50 degrees
Vertical +60 degrees
100
1000
10000
Frequency (Hz)


Normalized Vertical off-axis Response. Below the box
Attenuation in dB
5
0
-5
-10
-15
-20
-25
-30
Vertical -10 degrees
Vertical -20 degrees
Vertical -30 degrees
Vertical -40 degrees
Vertical -50 degrees
Vertical -60 degrees
100
1000
10000
Frequency (Hz)


Horizontal 1/3 Octave Polars
160
125
100


Horizontal 1/3 Octave Polars
315
250
200


Horizontal 1/3 Octave Polars
630
500
400


Horizontal 1/3 Octave Polars
1250
1000
800


Horizontal 1/3 Octave Polars
2500
2000
1600


Horizontal 1/3 Octave Polars
5000
4000
3150


Horizontal 1/3 Octave Polars
10000
8000
6300


Horizontal One Octave Polars


Vertical 1/3 Octave Polars
160
125
100


Vertical 1/3 Octave Polars
315
250
200


Vertical 1/3 Octave Polars
630
500
400


Vertical 1/3 Octave Polars
1250
1000
800


Vertical 1/3 Octave Polars
2500
2000
1600


Vertical 1/3 Octave Polars
5000
4000
3150


Vertical 1/3 Octave Polars
10000
8000
6300


Vertical One Octave Polars

C 32-L rot

Response 1W/1m



Impedance



Beamwidth vs. Frequency



Directivity Index and Q



Normalized Horizontal off-axis Response



Normalized Vertical off-axis Response. Above the box



Normalized Vertical off-axis Response. Below the box




Horizontal 1/3 Octave Polars
160
125
100


Horizontal 1/3 Octave Polars
315
250
200


Horizontal 1/3 Octave Polars
630
500
400


Horizontal 1/3 Octave Polars
1250
1000
800


Horizontal 1/3 Octave Polars
2500
2000
1600


Horizontal 1/3 Octave Polars
5000
4000
3150


Horizontal 1/3 Octave Polars
10000
8000
6300


Horizontal One Octave Polars


Vertical 1/3 Octave Polars
160
125
100


Vertical 1/3 Octave Polars
315
250
200


Vertical 1/3 Octave Polars
630
500
400


Vertical 1/3 Octave Polars
1250
1000
800


Vertical 1/3 Octave Polars
2500
2000
1600


Vertical 1/3 Octave Polars
5000
4000
3150


Vertical 1/3 Octave Polars
10000
8000
6300


Vertical One Octave Polars