

P 1108T

WEATHERPROOF TWO-WAY SPEAKER

DESCRIPTION

The P 1108T is a weatherproof full range, two-way speaker, suitable for a variety of professional indoor or outdoor applications. The high-frequency section includes a constant directivity CMD horn-loaded enclosure with a 1.4" voice coil RCF Precision neodymium compression driver for smooth, highly-controlled coverage. The low-frequency section features a 8" woofer with a 1.5" voice coil. The P 1108T also features a selectable line transformer for 100 V applications, with built-in LICC crossover, and Active Mosfet Compression Driver Protection (AMCDP). The single-piece rotomolded cabinet is fully UV protected and is equipped with M8 (4x) brass inserts and one electroplated steel U-bracket. The aluminum grille cover is powder coated with a water-repellent backing material, and a rotatable logo plate. The P 1108T meets IP 55 standard requirements (International Protection Rating).



FEATURES

- 100 W RMS power handling
- 121 dB max SPL
- 80 Hz ÷ 20000 Hz frequency range
- 8" woofer, 1.5" v.c.
- 1.4" v.c. neodymium compression driver
- 90° x 60° constant directivity
- Weatherproof IP55 cabinet with UV protection
- Aluminum grille
- Built in 100V line transformer

TECHNICAL SPECIFICATIONS

Acoustical specifications	Frequency Response (-10dB)	80 Hz ÷ 20000 Hz
	Max SPL @ 1m	121 dB
	Horizontal coverage angle	90°
	Vertical coverage angle	60°
	Directivity index Q	11
	System Sensitivity	95 dB
Power section	Amplification	Full Range
	Nominal Impedance	16 ohm
	Power Handling	100 W
	Peak Power Handling	400 W PEAK
	Protections	PTC
	Crossover Frequencies	2200 Hz
Transducers	Compression Driver	1 x 1.0", 1.4" v.c
	Woofer	1 x 8", 1.5" v.c
Input/Output section	Input connectors	Neoprene Cable
	Constant Voltage Transformer	100 V
	Power selection 1	60 W - 167 ohm
	Power selection 2	30 W - 333 ohm
	Power selection 3	15 W - 667 ohm
Standard compliance	IP protection grade	IP 55
	Safety agency	CE compliant
Physical specifications	Hardware	4 x M8 + U-Bracket and Pair of spacers
	Color	Grey, White - RAL 9003
Size	Height	266 mm / 10.47 inches
	Width	493 mm / 19.41 inches
	Depth	250 mm / 9.84 inches
	Weight	11.8 kg / 26.01 lbs
Shipping information	Package Height	534 mm / 21.02 inches
	Package Width	289 mm / 11.38 inches
	Package Depth	289 mm / 11.38 inches
	Package Weight	13.2 kg / 29.1 lbs

PART NUMBER

- **13100084**

P 1108T W

White - RAL 9003

EAN 8024530017538

- **13000203**

P 1108T

Grey

EAN 8024530008710



